

TWIST 11[®]

REF.
NTWIST / NTWISTC

**11 MM SEMI-STATIC ROPE
FLEXIBLE ANCHORAGE LINE**





TECHNICAL SPECIFICATIONS

diameter	Ø11 mm
weight	74 g/m
static elongation	1,8%
sheath number of plaits	32
breaking strength on 8 knot	≥ 1,5 kN
breaking strength	3,41 kN
material	100% polyamide

DESCRIPTION

The **TWIST 11[®]** rope of Ø 11 mm in polyamide high tenacity, is a semi-static multifunction rope, durable and easy to handle. It is also the flexible anchorage line for the mobile fall arrester **ASC'O[®]** and allows the user to be safe during his works at height.

ADVANTAGES

Very low static elongation, soft and easy to handle. Excellent grip.

USE

NTWIST : Use for all work at height requiring an **EN 1891-A** rope.
NTWISTC : Use as a flexible anchorage line for the **ASC'O[®]** guided type fall arrester according to **EN 353-2** standard.



REFERENCES

MODELS	STANDARD	REFERENCES	LENGTH	ENDINGS	CONNECTOR INCLUDED
NTWIST	EN 1891-A	NTWIST.50	50 m	✗	✗
		NTWIST.100	100 m		
		NTWIST.800	800 m		
NTWISTC	EN 353-2 <i>For use with ASC'O[®] guided type fall arrester</i>	NTWISTC.10.P	10 m		
		NTWISTC.15.P	15 m		
		NTWISTC.20.P	20 m		
		NTWISTC.30.P	30 m		

For any other length, contact us.