

fall
protection
only

neofeu)

by PMS GROUP
FABRICANT FRANÇAIS

serie
EDGE

REF.
NEO035

RETRACTABLE TYPE FALL ARRESTER 3,5 M



TESTED FOR
HORIZONTAL USE (EDIGE)

MAX
140 KG

MAXI USER
WEIGHT 140 KG




neofeu.com

REGULATION
| 2016 / 425

CERTIFICATION
| EN 360 : 2002

SHEETS
| RfU 11.060
| RfU 11.062



TECHNICAL SPECIFICATIONS

- Vertical and horizontal use up to 140 kg
- Total length 3,5 m
- 1 • High density polyethylene webbing, wide 25mm (R>22kN)
- 2 • Aluminum housing
- 3 • Energy absorber with a polyamide and polyester tearing strap of 31 mm breadth wrapped with a protective pouch
- Arrest force < 600 daN
- Static resistance ≥ 15 kN
- 4 • Swivel anchor hook on top fitted with (M) or (A) connector
- Automatic swivel connector with fall indicator in anodized aluminum (K) or (X)
- Weight : 1,65 kg (NEO035MK) - 2,0 kg (NEO035MX)

DESCRIPTION


Lightweight and compact fall arrester fitted with a self-retracting high density polyethylene webbing lanyard. Compatible in a horizontal use for a maximum load up to 140kg (user + equipment). The shock absorber is packaged in a protective pouch.

USE


Works on height with vertical fall hazards. Works in horizontal with fall hazard over a sharp edge (R = 0,5 mm).

The **NEO035** retractable type fall arrester is available in standard with the following steel or aluminum connectors :

(A)
NM16NS




(M)
NM20ALUB




swivel anchor side

(K)
NM26ELFA




(X)
NM28NET




shock absorber side

MINIMUM CLEARANCE AND FALL FACTORS



factor 1



horizontal use

REFERENCES	LENGTH AT REST (without connector)	EXTENDED LENGTH (without connector)	MINIMUM CLEARANCE		
			Maxi user weight	F1	Horizontale use
NEO035MK NEO035AK	695 mm	3500 mm	140 kg	≥ 2,60 m	≥ 5,00 m
	700 mm				
NEO035MX NEO035AX	760 mm				
	765 mm				