

neofeu)

Fall
Protection
Only

H2'O®

MAX
140 KG⁽¹⁾
📖

REF.
NUS57.H2O

HARNAIS ANTICHUTE



Produit
fabriqué avec
des **MATIÈRES
RECYCLÉES**


neofeu.com

RÈGLEMENT
| 2016 / 425

CERTIFICATION
| EN 361 : 2002

⁽¹⁾Le poids comprend l'utilisateur, ses outils et son matériel. Sous réserve d'utilisation d'un dispositif antichute associé testé à 140kg (voir mode d'emploi).



Les bouteilles plastiques usagées sont broyées puis modifiées en granulés.



Elles vont ensuite être transformées en fil puis tissées en sangle par exemple.



Les sangles, la plaque dorsale et le fil à coudre ont été fabriqués à partir de matières **100% recyclées**.



CARACTÉRISTIQUES TECHNIQUES

REF.
NUS57.H2O

- 1 • Sangles principales en **POLYESTER RECYCLÉ** 44 mm (R \geq 28,5kN)
 - 2 • Réglages des bretelles par le bas à l'aide des boucles rapides mâle/femelle en acier finition epoxy noir
 - 3 • Sangle bavaroise 44 mm et cuissardes à fermeture par boucles automatiques acier finition zingué noir avec témoin de fermeture
 - 4 • Point d'accrochage sternal sur anneau textile et point d'accrochage dorsal sur D métallique
 - 5 • Boucles anti-garrot brevetées en acier finition epoxy noir
 - 6 • Porte-longe amovible
 - 7 • Large plaque dorsale en **PLASTIQUE RECYCLÉ**
 - 8 • Témoins de chute de chaque côté
 - 9 • Pochette d'identification
- Résistance statique \geq 15 kN
• Masse : 1,20 kg
• **Emballage / 100% RECYCLABLE garanti SANS PLASTIQUE**

DESCRIPTION

Le harnais antichute **H2'O®** est le **1^{er} harnais Français** fabriqué avec des **matières recyclées**, comprenant 2 points d'accrochages: 1 sternal sur boucle textile et 1 dorsal sur D métallique. Il innove avec ses boucles anti-garrot au niveau des cuissardes qui réduisent l'effort sur l'utilisateur produit lors d'une chute. Il est équipé de boucles automatiques sur les cuissardes et bavaroise. Disponible en 3 tailles, il est facile à régler à l'aide de boucles plates sur les bretelles pour un ajustement en tirant vers le bas.

UTILISATION

Harnais antichute pour intervention avec un risque de chute. Adapté pour les secteurs de maintenance industrielle et bâtiment.



Références	Tailles					Masse
	Taille	Poitrine	Ceinture	Cuisses	Stature	
NUS57.H2O.S	S	80 - 105 cm	65 - 105 cm	45 - 65 cm	155 - 175 cm	1,15 kg
NUS57. H2O.ML	M/L	90 - 115 cm	85 - 120 cm	50 - 75 cm	165 - 188 cm	1,20 kg
NUS57. H2O.XL	XL	100 - 135 cm	105 - 130 cm	60 - 80 cm	170 - 200 cm	1,25 kg

neofeu)

Fall
Protection
Only

H2'O®

MAX
140 KG⁽¹⁾

REF.
NUS57.H2O

FULL BODY HARNESS




Product
made with
**RECYCLED
MATERIALS**


neofeu.com

REGULATION
| 2016 / 425

CERTIFICATION
| EN 361 : 2002

⁽¹⁾Weight included user, his tools and material. As far as it is associated with fall arrest device tested to 140kg (see user manual)



TECHNICAL SPECIFICATIONS

REF. NUS57.H2O

- 1 • Webbing in **RECYCLED POLYESTER** 44 mm wide (R_{≥28,5kN})
 - 2 • Shoulder straps adjustment pulling downwards with steel black powder coated quick buckles male/female
 - 3 • Chest strap and legs straps fastening through black zinc plated automatic buckles with locking indicator
 - 4 • Front fall arrest webbing loop and back fall arrest steel D ring
 - 5 • Patented anti-trauma buckles in steel black powder coated
 - 6 • Removable park lanyard
 - 7 • Large back plate in **RECYCLED PLASTIC**
 - 8 • Drop indicators on both side
 - 9 • Identification pouch
- Static resistance ≥ 15 kN
 • Weight : 1,20 kg
 • **RECYCLED** box / **100% RECYCLABLE** guaranteed **WITHOUT PLASTIC**

DESCRIPTION

The **H2'O®** full body harness is the **1st French harness** manufactured with **recycled materials**, including 2 fall arrest attachment points: 1 in the front with textile loop and 1 in the back with metallic D ring. It is an innovative harness with its anti trauma buckles on legs which reduces the arrest force in case of a fall. It is fitted with automatic buckles on chest and leg straps. Available in 3 sizes it can be easily adjusted by pulling downwards the shoulder straps through the quick buckles .

USE

Full body harness to use in case of fall hazard. Intended to maintenance works in industry and the construction area.



References	Size	Chest	Tailles			Weight
			Belt	Thighs	Stature	
NUS57.H2O.S	S	80 - 105 cm	65 - 105 cm	45 - 65 cm	155 - 175 cm	1,15 kg
NUS57. H2O.ML	M/L	90 - 115 cm	85 - 120 cm	50 - 75 cm	165 - 188 cm	1,20 kg
NUS57. H2O.XL	XL	100 - 135 cm	105 - 130 cm	60 - 80 cm	170 - 200 cm	1,25 kg