

CERTIFICATION : EN 361 : 2002 / EN 1497 : 2007 / REGULATION : 2016 / 425

TESTED
140KG


Comfort back pad

Orange coated back
D ring

Web loops front attachment

Automatic aluminum
buckles with locking
indicator

Fall indicator

Padded leg straps with
adjustment through
automatic buckles

Water repellent webbing

TECHNICAL SPECIFICATIONS

- Tested to 140 kg
 - Water repellent webbing in polyester 44 mm (R \geq 25 kN)
 - Shoulder straps adjustment with steel black epoxy coated quick buckles male/female
 - Chest strap 44 mm with automatic front buckle
 - Drop indicator showing at 300 daN
 - Large dorsal plate in polypropylene
 - Comfort pads on legs
 - Static resistance \geq 15 kN
 - Weight : 1,2 kg
- Standard models :
- Without back pad Réf. NUS67
 - With back pad Réf NUS67P

Other models available on request :

- Back extension strap of 300 mm Réf. NUS67EX
- Back pad + back extension strap Réf. NUS67EXP


USE

Full body harness to use in case of fall hazard. Intended to maintenance works in industry and the construction area.

DESCRIPTION

Full body harness VIT'O comfortable lightweight and safe, fits most of the bodies thanks to its high performance adjusting and locking systems.

TAILLE / SIZE



80 cm \leq Size S \leq 105 cm
90 cm \leq Size M-L \leq 115 cm
100 cm \leq Size XL \leq 135 cm

65 cm \leq Size S \leq 105 cm
85 cm \leq Size M-L \leq 120 cm
105 cm \leq Size XL \leq 135 cm

45 cm \leq Size S \leq 65 cm
50 cm \leq Size M-L \leq 75 cm
60 cm \leq Size XL \leq 80 cm

155 cm \leq Size S \leq 175 cm
165 cm \leq Size M-L \leq 188 cm
170 cm \leq Size XL \leq 200 cm