

CERTIFICATION : EN 795 : 2012 TYPE B / REGULATION : 2016 / 425

Anchor strap wide 30 mm  
high resistanceRatchet tensioner for  
fast adjustment of the  
webbing length

Screw gate connector

Choke strap through  
an aluminum ring**USE BY ONLY ONE USER**

2 standard lengths : 5 and 10 meters  
Other lengths from 1 to 10 meters available on request

**TECHNICAL SPECIFICATIONS**

- Anchor strap wide 30 mm
- Maximum deflection for Lan'o 10 m : 400 mm
- Sharp edge radius > 0,5 mm
- Static resistance >18 kN
- Maxi load in the horizontal direction to the structure : 9 kN
- Temperature of use : -35°C to +50°C

**DESCRIPTION**

LAN'O is designed to make a reliable anchor point around a structure which perimeter is between 50 cm and 1 meter. Made of high resistance polyamide web of 30 mm and tested on a radius  $\geq$  to 0.5 mm, LAN'O allows to make a solid anchor around skylights, chimneys, poles, IPN...

**USE**

Lan'o is intended to make an adjustable temporary anchor point around a structure so as to connect a fall arrester. To use on all industrial sites (construction, maintenance, ...).

**NB :**

Make sure that the anchorage structure has a minimum resistance of 18 kN and is without sharp edge.

