

# EASY SPEED

## GUIDED TYPE FALL ARRESTER ON FLEXIBLE ANCHORAGE LINE



### REGULATION

2016 / 425

### CERTIFICATION

EN 353-2 : 2002  
EN 12841 : 2006-A/B  
RFU 11.075

### TECHNICAL SPECIFICATIONS

- Made in aluminum
- Masse : 200 g

### DESCRIPTION

Versatile fall arrester on rope for work positioning, rope access and fall arrest. Lightweight, ergonomic, easy to carry and user friendly.

### USE

- It allows the safe ascent and descent along a vertical line, instantly locking in case of a fall.
- The travel along the rope is facilitated by the shape of the adjustment lever, that is activated by the connector when pushed upward during the use.
- Equipped with a two-position adjustment wheel (Rest/Go) to be used to set the mode: in the 'Go' position the device travels freely along the rope and it locks in case of a fall; in the 'Rest' position the device may be manually blocked above the user to minimize the potential fall factor.

### COMPATIBILITY

Standard	WLL	Rope	Component
1 EN 12841-A	140kg	NDRI0xxCT	Link20/40
2 EN 12841-B	100kg	NDRI0xxCT	Connecteur EN 362
3 EN 353-2	140kg	NDRI0xxCT	Conecteur EN 362 / Link20/40
4 RFU 11.075	120kg	NDRI0xxCT	Link20/40

