

NLR

MAX
140 KG



WORK POSITIONING LANYARD

REGULATION

2016 / 425

CERTIFICATION

EN 358 : 2018

TECHNICAL SPECIFICATIONS

- Maxi user weight 140 kg
 - 1 • Polyamide kernmantel rope Ø12mm
 - 2 • Aluminum alloy rope adjuster
 - 3 • Sewn terminations under protective sheath
 - 4 • Protective sleeve
 - 5 • Removable automatic triple lock connector in aluminum, opening 22mm
 - 6 • Automatic swivel connector in aluminum, with fall indicator, opening 21mm
- Weight NLR20MV : 775 g

Available in different lengths : 2, 3, 4 m.



DESCRIPTION

ERG'O is a work positioning lanyard in polyamide braided rope Ø12 mm. Fitted with an ergonomic rope adjuster in light alloy and a protective sleeve, the lanyard is equipped with triple lock connectors.

USE

Work positioning on a structure. Restraint system limiting access to a safe place.

Other available version



- 5.1 • Removable steel screw gate connector, opening 18mm
- 6.1 • Zinc plated steel screw gate connector, opening 18mm

- REF.**
- NLR20MV** Work positioning lanyard 2 m + 2 triple lock connectors in aluminum
 - NLR20AD** Work positioning lanyard 2 m + 2 steel connectors

Available in different lengths : 2, 3, 4 m.

Other connectors, contact us.

